

ALPHA™ -7

Wood Treatment Concentrate

FOR INDUSTRIAL USE ONLY

PRODUCT DATA

KOP-COAT, INC.

Industrial Wood Protection Products

FOR MORE INFORMATION, CONTACT KOP-COAT:
436 Seventh Avenue 5137 Southwest venue
Pittsburgh, PA 15219 St. Louis, MO 63110
412/227-2426 314/772-2200
412/227-2618 (Fax) 314/772-1710 (Fax)
Email: ippd@kop-coat.com
Ask Our Experts: www.kop-coat.com

Medical Emergencies: 1-800-548-0489

GENERAL:

ALPHA™ -7 is a neutral pH lumber brightener which is added to Kop-Coat's sapstain control treatments.

PRODUCT DESCRIPTION:

ALPHA™ -7 is for those customers who want brighter lumber at a neutral pH. ALPHA™ -7 is intended for use with sapstain control ready-to-use treating solution on lumber, logs and other commercial wood products requiring brighter lumber

MIXING INSTRUCTIONS:

Always thoroughly mix Alpha™ -7 with the treating solution to achieve a homogeneous milky solution. ALPHA™ -7 is typically used at dilution ratios of 100:1 in spray systems to 500:1 in dip tanks. It is effective on tank-stain, pre-stain and iron stains that develop during sawmilling.

APPLICATION:

Lumber should be totally immersed, flowcoated or sprayed to insure all surfaces are treated. Higher concentrations in spray applications are needed since less volume of solution is applied to the wood.

PACKAGING:

- Totes
- 55 gallon (208 liters) drums
- 5 gallon (18.9 liters) pails

STORAGE AND DISPOSAL:

Storage: KEEP OUT OF REACH OF CHILDREN. Keep container closed until used. Store in a cool, dry, well-ventilated area. Never use pressure to empty a drum. Do not store the concentrate in metal containers since product may react to produce flammable or explosive hydrogen gas.

Small spills: Absorb with sand, vermiculite, etc. Sweep up and place in a compatible chemical waste container.

Large spills: Dike with inert material: sand, vermiculite, etc. Transfer the solid and liquid to separate containers for recovery or disposal.

Dispose of in accordance with all Federal, State and local regulations.

COMBUSTIBLE. Class III B per OSHA Title 29 1910.106. DO NOT use, pour, spill or store near heat or open flame.

PHYSICAL PROPERTIES:

pH 7.0
Flash Point >200°F/93°C
Specific Gravity 0.93 @ 20°C
Appearance Dark amber liquid
Solubility in Water Soluble
Weight per Gallon 7.75 lbs./gal.

OTHER:

For health and safety information, please refer to ALPHA™ -7 Material Safety Data sheet.

KOP-COAT, INC.
Protection Products Division
PDALPHA -7 November 2000